

COMETE 2024 S3



Standard EN ISO 20345 : 2011

LEMAITRE

Safety since 1974



Sizes 36 to 48

Ref. COM2024S3

Product Highlights



- **Water-repellent full-grain leather upper:** a soft, resistant natural material

- **Heel shock absorption:** reduces fatigue and prevents RSI

- **Tongue with gusset** to prevent dust from entering the shoe



- **Comfort insole with activated charcoal:** anti-bacterial properties, odor neutralization. Humidity absorption system.



- **0% metal model** ideal for areas equipped with metal detectors (airports, warehouses).



- **Toe cap:** aluminium



- **Puncture-resistant midsole:** high-tenacity composite textile «0» penetration.



Anti-static sole GENESIS PU2D

- **Energy absorption at the heel for impulse with each new step**
- **Outsole designed for indoors and urban environments:** prone to frequent flexing
- **Raised heel** ; reinforced grip on ladder rungs
- **Arch support:** MSDs prevention
- **Front and rear reinforcements**

USE

- Light industry, logistics, handling and transport.



lemaitre-securite.com

Lemaitre takes care.



COMETE 2024 S3



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent full-grain leather
- **Tongue with gusset:** water-repellent leather
- **Lining:** micro-ventilated 3D textile
- **Collar:** water-repellent leather

Characteristics of the sole

- **Designation :** GENESIS
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,34 (standard $\geq 0,32$)
forward heel slip: 0,37 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,18 (standard $\geq 0,18$)
forward heel slip: 0,15 (standard $\geq 0,13$)

VARIANT



Concorde 2024 S3
CONC2024S3

Practical information

Weight of one shoe, size 42 : 650 g

AET N°ITASLNB23011740

Packaging

Sizes 36 to 40

shoebbox 315 x 220 x 125 mm

carton 635 x 445 x 325 mm

10 shoeboxes per carton

Sizes 41 to 48

shoebbox 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

36	3237154536360	43	3237154536438
37	3237154536377	44	3237154536445
38	3237154536384	45	3237154536452
39	3237154536391	46	3237154536469
40	3237154536407	47	3237154536476
41	3237154536414	48	3237154536483
42	3237154536421		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



(A) (E) (Fo)

S1P



(A) (E) (Fo)

S2



(A) (E) (Fo) (Wru)

S3



(A) (E) (Fo) (Wru)



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Shock absorption at the heel



Fuel oil-resistant outsole



Water penetration and water absorption resistant upper



Electrostatic discharge



Insulation against cold



Insulation against heat



Outsole resistance to hot contact



Water resistant



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



= SRA + SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE

Safety since 1974

Member of
SINAMAP



DON_LS 04 TDS 0162
update: 21/05/25